


Safety Data Sheet

Diesel Low Sulfur (LSD) and Ultra Low Sulfur Diesel (ULSD)

NFPA: Flammability



SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Diesel Low Sulfur (LSD) and Ultra Low Sulfur Diesel (ULSD)

Synonyms : CARB Diesel, 888100004478

MSDS Number 888100004478 **Version** 2.31

Product Use Description

Company For: Tesoro Refining & Marketing Co.
19100 Ridgewood Parkway, San Antonio, TX 78259

Tesoro Call Center (877) 783-7676 **Chemtrec (Emergency Contact)** (800) 424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classifications

- Flammable Liquid – Category 3
- Skin Irritation – Category 2
- Eye Irritation – Category 2B
- Aspiration Hazard – Category 1
- Carcinogenicity – Category 2
- Acute Toxicity - Inhalation – Category 4
- Chronic Aquatic Toxicity – Category 2

Pictograms



Signal Word

Danger

Hazard Statements

Flammable liquid and vapor.
May be fatal if swallowed and enters airways – do not siphon diesel by mouth.
Causes skin irritation.
Causes eye irritation.
Suspected of causing skin cancer if repeated and prolonged skin contact occurs.
Suspected of causing cancer in the respiratory system if repeated and prolonged over-exposure by inhalation occurs.
May cause damage to liver, kidneys and nervous system by repeated and prolonged inhalation.

Toxic if inhaled.
May cause drowsiness or dizziness by inhalation.
Toxic to aquatic life with long lasting effects.

Precautionary statements**Prevention**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, sparks, open flames, welding and hot surfaces.
No smoking.
Keep container tightly closed.
Ground and/or bond container and receiving equipment.
Use explosion-proof electrical equipment.
Use only non-sparking tools if tools are used in flammable atmosphere.
Take precautionary measures against static discharge.
Wear gloves, eye protection and face protection as needed to prevent skin and eye contact with liquid.
Wash hands or liquid-contacted skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Avoid breathing vapors or mists.
Use only outdoors or in a well-ventilated area.

Response

In case of fire: Use dry chemical, CO₂, water spray or fire fighting foam to extinguish.
If swallowed: Immediately call a poison center, doctor, hospital emergency room, medical clinic or 911. Do NOT induce vomiting. Rinse mouth.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
If in eye: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin or eye irritation persists, get medical attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call or doctor or emergency medical provider. See Section 4 and Section 11 for medical treatment information.

Storage

Store in a well ventilated place. Keep cool. Store locked up. Keep container tightly closed. Use only approved containers.

Disposal

Dispose of contents/containers to approved disposal site in accordance with local, regional, national, and/or international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
Fuels, diesel, No 2; Gasoil - unspecified	68476-34-6	100%
Nonane	111-84-2	0 - 5%
Naphthalene	91-20-3	0 - 1%

1,2,4-Trimethylbenzene	95-63-6	0 - 2%
Xylene	1330-20-7	0 - 2%
Sulfur	7704-34-9	15 ppm maximum

SECTION 4. FIRST AID MEASURES

- Inhalation** : Move to fresh air. Give oxygen. If breathing is irregular or stopped, administer artificial respiration. Seek medical attention immediately.
- Skin contact** : Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Wash contaminated clothing before re-use. If skin irritation persists, seek medical attention immediately.
- Eye contact** : Remove contact lenses. Rinse thoroughly with plenty of water for at least 15 minutes. If symptoms persist, seek medical attention.
- Ingestion** : Do not induce vomiting without medical advice. If a person vomits when lying on his back, place him in the recovery position. Seek medical attention immediately.
- Notes to physician** : Symptoms: Dizziness, Discomfort, Headache, Nausea, Disorder, Vomiting, Lung edema, Liver disorders, Kidney disorders. Aspiration may cause pulmonary edema and pneumonitis.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media** : SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray or fire fighting foam. LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers. Keep containers and surroundings cool with water spray.
- Specific hazards during fire fighting** : Fire Hazard Do not use a solid water stream as it may scatter and spread fire. Cool closed containers exposed to fire with water spray.
- Special protective equipment for fire-fighters** : Wear self-contained breathing apparatus and protective suit. Use personal protective equipment.
- Further information** : Exposure to decomposition products may be a hazard to health. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to contain spill areas. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact. Ensure adequate ventilation. Use personal protective equipment.

- Environmental precautions** : Carefully contain and stop the source of the spill, if safe to do so. Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection. Discharge into the environment must be avoided. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up** : Take up with sand or oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal - caution, flammable vapors may accumulate in closed containers. Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

SECTION 7. HANDLING AND STORAGE

- Precautions for safe handling** : Keep away from fire, sparks and heated surfaces. No smoking near areas where material is stored or handled. The product should only be stored and handled in areas with intrinsically safe electrical classification.
- : Hydrocarbon liquids including this product can act as a non-conductive flammable liquid (or static accumulators), and may form ignitable vapor-air mixtures in storage tanks or other containers. Precautions to prevent static-initated fire or explosion during transfer, storage or handling, include but are not limited to these examples:
- (1) Ground and bond containers during product transfers. Grounding and bonding may not be adequate protection to prevent ignition or explosion of hydrocarbon liquids and vapors that are static accumulators.
 - (2) Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil or diesel) is loaded into tanks previously containing low flash point products (such as gasoline or naphtha).
 - (3) Storage tank level floats must be effectively bonded.
- For more information on precautions to prevent static-initated fire or explosion, see NFPA 77, Recommended Practice on Static Electricity (2007), and API Recommended Practice 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents (2008).
- Conditions for safe storage, including incompatibilities** : Keep away from flame, sparks, excessive temperatures and open flame. Use approved containers. Keep containers closed and clearly labeled. Empty or partially full product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose containers to sources of ignition. Store in a well-ventilated area. The storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code". The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks In Flammable and Combustible Liquid Service" and API RP 2015 "Cleaning Petroleum Storage Tanks".
- : Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure.
- Keep away from food, drink and animal feed. Incompatible with oxidizing agents. Incompatible with acids.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

List	Components	CAS-No.	Type:	Value
OSHA Z1	Xylene	1330-20-7	PEL	100 ppm 435 mg/m3
	Naphthalene	91-20-3	PEL	10 ppm 50 mg/m3
ACGIH	Diesel Fuel	68476-30-2	TWA	100 mg/m3
	Xylene	1330-20-7	TWA	100 ppm
		1330-20-7	STEL	150 ppm
	Naphthalene	91-20-3	TWA	10 ppm
		91-20-3	STEL	15 ppm
	Nonane	111-84-2	TWA	200 ppm

- Engineering measures** : Use adequate ventilation to keep gas and vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces. Use only intrinsically safe electrical equipment approved for use in classified areas.
- Eye protection** : Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.
- Hand protection** : Gloves constructed of nitrile, neoprene, or PVC are recommended. Consult manufacturer specifications for further information.
- Skin and body protection** : If needed to prevent skin contact, chemical protective clothing such as of DuPont TyChem®, Saranex or equivalent recommended based on degree of exposure. The resistance of specific material may vary from product to product as well as with degree of exposure.
- Respiratory protection** : A NIOSH/ MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection. Use a NIOSH/ MSHA-approved positive-pressure supplied-air respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.
- Work / Hygiene practices** : Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Use good personal hygiene practices. Avoid repeated and/or prolonged skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Do not use as a cleaning solvent on the skin. Do not use solvents or harsh abrasive skin cleaners for washing this product from exposed skin areas. Waterless hand cleaners are effective. Promptly remove contaminated clothing and launder before reuse. Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear to straw colored liquid
Odor	Characteristic petroleum or kerosene-like odor
Odor threshold	0.1 - 1 ppm typically reported
pH	Not applicable
Melting point/freezing point	Gel point can be about -15°F; freezing requires laboratory conditions
Initial boiling point & range	154 - 372 °C (310° - 702 °F)
Flash point	38°C Minimum for #1 Diesel, 52°C Minimum for #2 Diesel
Evaporation rate	Higher initially and declining as lighter components evaporate
Flammability (solid, gas)	Flammable vapor released by liquid
Upper explosive limit	6.5 %(V)
Lower explosive limit	0.6 %(V)
Vapor pressure	< 2 mm Hg at 20 °C
Vapor density (air = 1)	> 4.5
Relative density (water = 1)	0.86 g/mL
Solubility (in water)	0.0005 g/100 mL
Partition coefficient (n-octanol/water)	> 3.3 as log Pow
Auto-ignition temperature	257 °C (495 °F)
Decomposition temperature	Will evaporate or boil and possibly ignite before decomposition occurs.
Kinematic viscosity	1 to 6 mm ² /s range reported for No.1 or No.2 diesel at ambient temperatures
Conductivity (conductivity can be reduced by environmental factors such as a decrease in temperature)	Diesel Fuel Oils at terminal load rack: At least 25 pS/m Ultra Low Sulfur Diesel (ULSD) without conductivity additive: 0 pS/m to 5 pS/m ULSD at terminal load rack with conductivity additive: At least 50 pS/m JP-8 at terminal load rack: 150 pS/m to 600 pS/m

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapors may form explosive mixture with air. Hazardous polymerization does not occur.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Can react with strong oxidizing agents, peroxides, acids and alkalies. Do not use with Viton or Fluorel gaskets or seals.
Conditions to avoid	Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources. Avoid static charge accumulation and discharge (see Section 7).
Hazardous decomposition products	Ignition and burning can release carbon monoxide, carbon dioxide, non-combusted hydrocarbons (smoke) and, depending on formulation, trace amounts

of sulfur dioxide. Diesel exhaust particals may be a lung hazard (see Section 11).

SECTION 11. TOXICOLOGICAL INFORMATION

Inhalation	: Vapors or mists from this material can irritate the nose, throat, and lungs, and can cause signs and symptoms of central nervous system depression, depending on the concentration and duration of exposure.
Skin contact	Skin irritation leading to dermatitis may occur upon prolonged or repeated contact. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are repeatedly exposed. Long-term, repeated skin contact may cause skin cancer.
Eye contact	Eye irritation may result from contact with liquid, mists, and/or vapors.
Ingestion	Harmful or fatal if swallowed. Do NOT induce vomiting. This material can irritate the mouth, throat, stomach, and cause nausea, vomiting, diarrhea and restlessness. Aspiration hazard if liquid is inhaled into lungs, particularly from vomiting after ingestion. Aspiration may result in chemical pneumonia, severe lung damage, respiratory failure and even death.
Target organs	Central nervous system, Eyes, Skin, Kidney, Liver
Further information	Studies have shown that similar products produce skin cancer or skin tumors in laboratory animals following repeated applications without washing or removal. The significance of this finding to human exposure has not been determined. Other studies with active skin carcinogens have shown that washing the animal's skin with soap and water between applications reduced tumor formation. Repeated over-exposure may cause liver and kidney injury IARC classifies whole diesel fuel exhaust particulates as carcinogenic to humans (Group 1). NIOSH regards whole diesel fuel exhaust particulates as a potential cause of occupational lung cancer based on animal studies and limited evidence in humans.

Component:

Fuels, diesel, No 2; Gasoil - unspecified	68476-34-6	<u>Acute oral toxicity:</u> LD50 rat Dose: 5,001 mg/kg <u>Acute dermal toxicity:</u> LD50 rabbit Dose: 2,001 mg/kg <u>Acute inhalation toxicity:</u> LC50 rat Dose: 7.64 mg/l Exposure time: 4 h <u>Skin irritation:</u> Classification: Irritating to skin. Result: Severe skin irritation <u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation
Nonane	111-84-2	<u>Acute oral toxicity:</u> LD50 mouse Dose: 218 mg/kg <u>Acute inhalation toxicity:</u> LC50 rat Exposure time: 4 h
Naphthalene	91-20-3	<u>Acute oral toxicity:</u> LD50 rat Dose: 2,001 mg/kg <u>Acute dermal toxicity:</u> LD50 rat Dose: 2,501 mg/kg

		<u>Acute inhalation toxicity:</u> LC50 rat Dose: 101 mg/l Exposure time: 4 h
		<u>Skin irritation:</u> Classification: Irritating to skin. Result: Mild skin irritation
		<u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation
		<u>Carcinogenicity:</u> N11.00422130
1,2,4-Trimethylbenzene	95-63-6	<u>Acute inhalation toxicity:</u> LC50 rat Dose: 18 mg/l Exposure time: 4 h
		<u>Skin irritation:</u> Classification: Irritating to skin. Result: Skin irritation
		<u>Eye irritation:</u> Classification: Irritating to eyes. Result: Eye irritation
Xylene	1330-20-7	<u>Acute oral toxicity:</u> LD50 rat Dose: 2,840 mg/kg
		<u>Acute dermal toxicity:</u> LD50 rabbit Dose: ca. 4,500 mg/kg
		<u>Acute inhalation toxicity:</u> LC50 rat Dose: 6,350 mg/l Exposure time: 4 h
		<u>Skin irritation:</u> Classification: Irritating to skin. Result: Mild skin irritation Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
		<u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation
<u>Carcinogenicity</u>		
NTP	Naphthalene	(CAS-No.: 91-20-3)
IARC	Naphthalene	(CAS-No.: 91-20-3)
OSHA	No component of this product which is present at levels greater than or equal to 0.1 % is identified as a carcinogen or potential carcinogen by OSHA.	
CA Prop 65	WARNING! This product contains a chemical known to the State of California to cause cancer. naphthalene (CAS-No.: 91-20-3)	

SECTION 12. ECOLOGICAL INFORMATION

Additional ecological information : Keep out of sewers, drainage areas, and waterways. Report spills and releases, as applicable, under Federal and State regulations.

Component:

Diesel	68476-34-6	<u>Toxicity to fish:</u> LC50 Species: Jordanella floridae Dose: 54 mg/l
--------	------------	---

Exposure time: 96 h

Toxicity to crustacea:

Species: Palaemonetes pugio

TLm (48 hour) = 3.4 mg/l

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal : Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14. TRANSPORT INFORMATION**CFR**

Proper shipping name : DIESEL FUEL
UN-No. : UN1202 (NA 1993)
Class : 3
Packing group : III

TDG

Proper shipping name : DIESEL FUEL
UN-No. : UN1202 (NA 1993)
Class : 3
Packing group : III

IATA Cargo Transport

UN UN-No. : UN1202 (NA 1993)
Description of the goods : DIESEL FUEL
Class : 3
Packaging group : III
ICAO-Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (cargo aircraft) : Y344

IATA Passenger Transport

UN UN-No. : UN1202 (NA 1993)
Description of the goods : DIESEL FUEL
Class : 3
Packaging group : III
ICAO-Labels : 3
Packing instruction (passenger aircraft) : 355
Packing instruction (passenger aircraft) : Y344

IMDG-Code

UN-No. : UN 1202 (NA 1993)
Description of the goods : DIESEL FUEL
Class : 3
Packaging group : III
IMDG-Labels : 3

EmS Number : F-E S-E
Marine pollutant : No

SECTION 15. REGULATORY INFORMATION**: CERCLA SECTION 103 and SARA SECTION 304 (RELEASE TO THE ENVIRONMENT)**

The CERCLA definition of hazardous substances contains a "petroleum exclusion" clause which exempts crude oil. Fractions of crude oil, and products (both finished and intermediate) from the crude oil refining process and any indigenous components of such from the CERCLA Section 103 reporting requirements. However, other federal reporting requirements, including SARA Section 304, as well as the Clean Water Act may still apply.

TSCA Status : On TSCA Inventory

DSL Status : All components of this product are on the Canadian DSL list.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA III US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

Components**CAS-No.**

Xylene

1330-20-7

1,2,4-Trimethylbenzene

95-63-6

Naphthalene

91-20-3

PENN RTK US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Components**CAS-No.**

Nonane

111-84-2

Naphthalene

91-20-3

1,2,4-Trimethylbenzene

95-63-6

xylene

1330-20-7

Fuels, diesel, No 2; Gasoil - unspecified

68476-34-6

MASS RTK US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Components**CAS-No.**

Xylene

1330-20-7

1,2,4-Trimethylbenzene

95-63-6

Naphthalene

91-20-3

Nonane

111-84-2

NJ RTK US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

Components**CAS-No.**

Nonane

111-84-2

Naphthalene	91-20-3
1,2,4-Trimethylbenzene	95-63-6
Xylene	1330-20-7
Fuels, diesel, No 2; Gasoil - unspecified	68476-34-6

California Prop. 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

Naphthalene	91-20-3
-------------	---------

SECTION 16. OTHER INFORMATION

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

10/29/2012

1153, 1250, 1443, 1454, 1814, 1815, 1866, 1925